

WIND
RESISTANCE




HEAVY
DUTY



RELIABLE



LOW
MANTEINANCE



DOUBLE
CURTAIN

MEGAPACK

DESCRIPTION

MEGAPACK fold up door has been designed for outdoor industrial environments, where there are large openings for hangars and shipyards.

MEGAPACK industrial door guarantees long durability, energy saving and reliability with minimum maintenance.

Each industrial door is individually designed to adapt to the building on which it is to be installed and guarantees excellent wind resistance thanks to the mantle formed by two polyester fabrics connected by horizontal aluminium trusses.



EN13241/CE ADVANTAGES APPLICATION

Fold up door with conical columns and double curtain ideal for:

- ✓ Industry (outside)
- ✓ Shipyard
- ✓ Hangar
- ✓ Waste treatment

- ✓ Class 4 - 144 km/h
- ✓ Energy savings
- ✓ Double PVC curtains
- ✓ Minimal maintenance


| Standard | Rif. | Test acc. | Results |
|-----------------------|----------|-----------|-----------|
| Wind load | EN 12424 | EN 12444 | Class 4 |
| Safe openings | EN 12453 | EN 12445 | ✓ |
| Mechanical resistance | EN 12604 | EN 12605 | ✓ |
| Unintended movements | EN 12604 | EN 12605 | ✓ |
| Performance (cycles) | EN 12604 | EN 12605 | 1.000.000 |

VALUES CAN CHANGE DEPENDING ON DOOR DIMENSIONS


FEATURES

| | |
|--------------------------------|---|
| Maximum dimensions | W 20.000 mm x H 15.000 mm |
| Speed | Max opening speed up to 0,3 m/s |
| | Closing speed 0,3 m/s |
| Wind resistance | Up to Class 4 / higher classes on a project basis |
| Structure | Not self-supporting |
| Frame / motor cover hood | Standard : Galvanized Steel |
| Curtain | Standard : PVC curtain fabric 900 gr/m ² |
| | Optional : Insulated curtain PVC 1350 gr/m ² |
| Control panel | Standard : Powder coated Steel box IP54 (400 x 500 x 2000 mm) |
| | Optional : the cabinet may be equipped with electro-mechanical system with possibility to be controlled by a PLC system |
| | Contactors (50 Hz) |
| | Power supply 3-ph, 400V |
| | Power supply 24VAC for auxiliary accessories |
| Safeties | Standard : WiFi safety edge IP65 |
| Emergency opening | Standard : Mechanical |
| Advising operative temperature | -30°C +70°C |
| Cycles (EN 12604) | 1.000.000 (tested) |

LIFTING BELTS - STRAPS




SLIDING GLASS DOOR LEAF



MEGAPACK: 40 m x 18 m



TOP HEADING



AVAILABLE COLOURS

Simil RAL 9010



Simil RAL 1015



Simil RAL 1003



Simil RAL 2008



Simil RAL 3002



Simil RAL 6026



Simil RAL 9006



Simil RAL 7042



Simil RAL 7037



Simil RAL 7035



Simil RAL 5012



Simil RAL 5002

